

**Pocket filter**  
**AIRsyntex PM10 55%**  
**592 x 592 x 535 12 poc.**




Filter class acc. to ISO 16890 EN 779:2012	Particle efficiency	Energy consumption	Energy class <small>Threshold reference scale year 2019: (RS 4/C/001-2019)</small>
ISO ePM10 55% M5	ePM <sub>1</sub> 10 % ePM <sub>2,5</sub> 25 % ePM <sub>10</sub> 55 %	> 1.100 kWh/year	E



**Operating conditions:**

Max. humidity resistance	100%
Max. temperature	70°C
Recommended final pressure drop	300 Pa
Potential nominal air flow (short term usage possible)	1,25 x nominal air flow
Fire behaviour	DIN 53438-3 (F1)

Medium Synthetic-progressive microfiber  
 Media color ■ Brown




Please note: in EUROVENT database, the depth of the model is extended by 25 mm

WIDTH [mm]	HEIGHT [mm]	DEPTH [mm]	Number of pockets	Filter area [m <sup>2</sup> ]	Recommended nominal air flow [m <sup>3</sup> /h]	Initial pressure drop [Pa]
<b>592</b>	<b>592</b>	<b>535</b>	<b>12</b>	<b>7,6</b>	<b>3.400</b>	<b>65</b>
490	592	535	10	6,3	2.800	65
287	592	535	6	3,8	1.700	65
592	287	535	12	3,7	1.700	65
592	490	535	12	6,3	2.800	65
287	287	535	6	1,8	800	65
592	892	535	12	11,5	5.100	65
490	892	535	10	9,5	4.300	65
287	892	535	6	5,7	2.600	65

**Product benefits:**

- Multi-layer structure of the filter media
- Shatter-proof synthetic fibres
- Welded continuous pockets
- Optimal pocket opening
- Efficient and economical at the same time
- Testing for paint compatibility by Fraunhofer IPA
- For use in air-conditioning and ventilation systems of all kinds

**Initial pressure drop 592x592x535x12poc.**



**Versions:**

- Plastic frame: 25 mm
- Metal frame: 20 mm, 25 mm
- Special sizes on request
- Version with plastic frame fully incinerable
- Optional with foamed hygiene gasket



**Notice:**

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.