

**Pocket filter**  
**AIRsyntax PM1 65%**  
**592 x 592 x 635 10 poc.**



Filter class acc. to ISO 16890 EN 779:2012	Particle efficiency	Energy consumption	Energy class <small>Threshold reference scale year 2019: (RS 4/C/001-2019)</small>
ISO ePM1 65% F8	ePM <sub>1</sub> 65 % ePM <sub>2,5</sub> 70 % ePM <sub>10</sub> 90 %	> 2.050 kWh/year	E




Similar to picture

**Operating conditions:**

Max. humidity resistance	100%
Max. temperature	70°C
Recommended final pressure drop	300 Pa
Max. airflow (short term usage possible)	1,25 x nominal air flow
Fire behaviour	DIN 53438-3 (F1)

Medium Synthetic-progressive microfiber

Media color White




Please note: in EUROVENT database, the depth of the model is extended by 25 mm

WIDTH [mm]	HEIGHT [mm]	DEPTH [mm]	Number of pockets	Filter area [m <sup>2</sup> ]	Recommended nominal air flow [m <sup>3</sup> /h]	Initial pressure drop [Pa]
<b>592</b>	<b>592</b>	<b>635</b>	<b>10</b>	<b>7,5</b>	<b>3.400</b>	<b>165</b>
490	592	635	8	6	2.700	165
287	592	635	5	3,8	1.700	165
592	287	635	10	3,6	1.600	165
592	490	635	10	6,2	2.800	165
287	287	635	5	1,8	800	165
592	892	635	10	11,3	5.100	165
490	892	635	8	9,1	4.100	165
287	892	635	5	5,7	2.600	165

**Product benefits:**

- Multi-layer structure of the filter media
- Shatter-proof synthetic fibres
- Welded continuous pockets
- Optimal pocket opening
- Efficient and economical at the same time
- Filter media tested according to OEKO-TEX® Standard 100 for harmful chemical substances (17.0.25812)
- Testing for paint compatibility by Fraunhofer IPA
- For use in air-conditioning and ventilation systems of all kinds

**Initial pressure drop 592x592x635x10poc.**



**Versions:**

- Plastic frame: 25 mm
- Metal frame: 20 mm, 25 mm
- Special sizes on request
- Version with plastic frame fully incinerable
- Optional with foamed hygiene gasket



**Notice:**

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.