Technical datasheet

Pocket filter Ex-Protect PM10 65%


592 x 592 x 600 8 poc.



Filter class acc. to ISO 16890 EN 779:2012	Particle efficiency		Energy consumption	Energy class Treshold reference scale year 2019: (RS 4/C/001-2019)
ISO ePM10 65% M6	ePM ₁ ePM _{2,5} ePM ₁₀	10 % 25 % 65 %	> 1.200 kWh/year	Е

Operating conditions:					
Max. humidity resistance	100%				
Max. temperature	70°C				
Recommended final pressure drop	300 Pa				
Potential nominal air flow (short term usage possible)	1,25 x nominal air flow				
Fire behaviour	DIN 53438-3 (F3)				





WIDTH	HEIGHT	DEPTH	Number of pockets	Filter area	Recommended nominal air flow	Initial pressure drop
[<i>mm</i>]	[mm]	[mm]		[<i>m</i> ²]	[m ³ /h]	[Pa]
592	592	600	8	5,7	3.400	90
490	592	600	6	4,3	2.600	90
287	592	600	4	2,8	1.700	90
592	287	600	8	2,8	1.700	90
592	490	600	8	4,7	2.800	90
287	287	600	4	1,4	850	90

Product benefits:

- Shatter-proof synthetic fibres with integrated metal mesh
- Individual stitched pockets
- Electroconductive media with integrated metal mesh
- Ex-Protect filters will not gain electrostatic charge
- For air filtration in aerial engineering plants with dangerous, combustible atmospheres (mixtures of air and burnable gases or steams)


• Device category 2, group II according to EU directive 2014/34 / EU and EN 1127-1: 2011, EN ISO 80079-36: 2016, EN ISO 80079-37: 2016, type of protection Ex "c" suitable for atmospheres with gas, steam, fog or dust.

• Suitable for use in potentially explosive areas of zones 1, 2 and 21, 22 in accordance with EU Directive 1999/92 / EC. (Conductive



dusts are to be excluded from the application)

Initial pressure drop 592x592x600x8poc.



Air flow [m³/h]



- Sewn construction
- Special sizes on request
- With galvanized metal frame (inner and outer frames)
- Available with grounding flag or grounding pin
- Manufacturers declaration is included with each filter





Notice:

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifikations without notice.

VOLZ Luftfilter GmbH & Co. KG

Manfred-Volz-Straße 3 / D-72160 Horb am Neckar / Tel.: +49 7451 5516-0

www.volzfilters.com

TSM / SAC / 2021.04.07 Replaces all previous versions of this data sheet

TDS V0.3.4 / APP V0.6.1