

Pocket filter  
PROsyntex PM2,5 60%  
592 x 592 x 635 12 poc.




Filter class acc. to ISO 16890  EN 779:2012	Particle efficiency	Energy consumption	Energy class <small>Threshold reference scale year 2019: (RS 4/C/001-2019)</small>
ISO ePM <sub>2,5</sub> 60% F7	ePM <sub>1</sub> 50 % ePM <sub>2,5</sub> 60 % ePM <sub>10</sub> 90 %	1.400 kWh/year	D

Operating conditions:	
Max. humidity resistance	100%
Max. temperature	70°C
Recommended final pressure drop	300 Pa
Max. airflow (short term usage possible)	1,25 x nominal air flow
Fire behaviour	DIN 53438-3 (F1)



Similar to picture

Medium Synthetic-progressive microfiber  
Media color Pink




Please note: in EUROVENT database, the depth of the model is extended by 25 mm

WIDTH [mm]	HEIGHT [mm]	DEPTH [mm]	Number of pockets	Filter area [m²]	Recommended nominal air flow [m³/h]	Initial pressure drop [Pa]
592	592	635	12	9	3.400	115
490	592	635	10	7,5	2.800	115
287	592	635	6	4,5	1.700	115
592	287	635	12	4,4	1.700	115
592	490	635	12	7,5	2.800	115
287	287	635	6	2,2	850	115
592	892	635	12	13,6	5.100	115
490	892	635	10	11,3	4.300	115
287	892	635	6	6,8	2.600	115

Product benefits:

- Multi-layer structure of filter media consisting of shatter-proof synthetic fibres
- Ultrasonic welded continuous pockets with optimal distribution of incoming flow (pocket fitting)
- Low pressure drop and high dust holding capacity
- Filter media tested according to OEKO-TEX® Standard 100 for harmful chemical substances (17.0.25812)
- the optional BIOSTATIC version can be used when hygiene demands are high and in environments with increased air humidity
- Tested for paint compatibility by Fraunhofer IPA institute (doesn't apply to the biostatic version)
- For use in air-conditioning and ventilation systems of all kinds as well as in painting technology



- Versions:
- Plastic frame: 25 mm
  - Metal frame: 20 mm, 25 mm
  - Special sizes on request
  - Version with plastic frame fully incinerable
  - Optional with foamed hygiene gasket
  - Optional **BIOSTATIC version**: the ingredients located within the synthetic fibers „Silane Quaternary Ammonium Salt“ and "Silver-Phosphate-Glass" (BIOCIDE) prevent odors and the formation of microorganisms on the filter which is harmful to the health

Notice:  
All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.