

**Pocket filter**  
**Polyester ISO Coarse 50%**  
**592 x 592 x 360 6 poc.**




Filter class acc. to ISO 16890	EN 779: 2012
ISO Coarse 50%	G3



**Operating conditions:**

Max. humidity resistance	100%
Max. temperature	70°C
Recommended final pressure drop	200 Pa
Potential nominal air flow (short term usage possible)	1,25 x nominal air flow
Fire behaviour	DIN 53438-3 (F1)

Medium Polyester  
 Media color White




WIDTH [mm]	HEIGHT [mm]	DEPTH [mm]	Number of pockets	Filter area [m²]	Recommended nominal air flow [m³/h]	Initial pressure drop [Pa]
<b>592</b>	<b>592</b>	<b>360</b>	<b>6</b>	<b>2,6</b>	<b>3.400</b>	<b>40</b>
490	592	360	5	2,1	2.700	40
287	592	360	3	1,3	1.700	40
592	287	360	6	1,2	1.600	40
592	490	360	6	2,1	2.700	40
287	287	360	3	0,6	800	40
592	892	360	6	3,9	5.100	40
490	892	360	5	3,2	4.200	40
287	892	360	3	1,9	2.500	40

**Product benefits:**

- Progressive structure
- Shatter-proof synthetic fibres
- Welded continuous pockets
- Edge welding for higher density and pressure load
- Self-supporting pockets
- Optimal distribution of incoming flow
- Testing for paint compatibility by Fraunhofer IPA
- For use in air-conditioning and ventilation systems of all kinds as well as in painting technology

**Initial pressure drop 592x592x360x6poc.**



**Versions:**

- Plastic frame: 25 mm
- Metal frame: 20 mm, 25 mm
- Special sizes on request
- Version with plastic frame fully incinerable
- Optional with foamed hygiene gasket



**Notice:**

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.