

**Pocket filter**  
**Polyester ISO Coarse 70%**  
**592 x 592 x 360 6 poc.**




Filter class acc. to ISO 16890	EN 779: 2012
ISO Coarse 70%	M5



**Operating conditions:**

Max. humidity resistance	100%
Max. temperature	70°C
Recommended final pressure drop	200 Pa
Potential nominal air flow (short term usage possible)	1,25 x nominal air flow
Fire behaviour	DIN 53438-3 (F1)

Medium Polyester  
 Media color  White




WIDTH [mm]	HEIGHT [mm]	DEPTH [mm]	Number of pockets	Filter area [m²]	Recommended nominal air flow [m³/h]	Initial pressure drop [Pa]
<b>592</b>	<b>592</b>	<b>360</b>	<b>6</b>	<b>2,6</b>	<b>2.000</b>	<b>25</b>
490	592	360	5	2,1	1.600	25
287	592	360	3	1,3	1.000	25
592	287	360	6	1,2	900	25
592	490	360	6	2,1	1.600	25
287	287	360	3	0,6	450	25
592	892	360	6	3,9	3.000	25
490	892	360	5	3,2	2.500	25
287	892	360	3	1,9	1.500	25

**Product benefits:**

- Progressive structure
- Shatter-proof synthetic fibres
- Welded continuous pockets
- Edge welding for higher density and pressure load
- Self-supporting pockets
- Optimal distribution of incoming flow
- BIOSTATIC version can be used when hygiene demands are high and in environments with increased air humidity
- Testing for paint compatibility by Fraunhofer IPA (not valid for the biostatic version)
- For use in air-conditioning and ventilation systems of all kinds as well as in painting technology

**Initial pressure drop 592x592x360x6poc.**



**Versions:**

- Plastic frame: 25 mm
- Metal frame: 20 mm, 25 mm
- Special sizes on request
- Version with plastic frame fully incinerable
- Optional with foamed hygiene gasket
- Optional **BIOSTATIC version**-the ingredient located within the synthetic fibers „BIO-Hunter RX-106“ (BIOZIDE) prevents odors and the formation of microorganisms on the filter which is harmful to the health



**Notice:**

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.