

# **Pocket filter** Polyester PM10 50% 592 x 592 x 360 6 poc.









Filter class acc. to ISO 16890 EN 779:2012	Particle efficiency		Energy consumption	Energy class Treshold reference scale year 2019: (RS 4/C/001-2019)	
ISO ePM10 50% M5	ePM <sub>1</sub> ePM <sub>2,5</sub> ePM <sub>10</sub>	3 % 10 % 50 %	1.100 kWh/year	D	

Operating conditions:				
Max. humidity resistance	100%			
Max. temperature	70°C			
Recommended final pressure drop	300 Pa			
Max. airflow (short term usage possible)	1,25 x nominal air flow			
Fire behaviour	DIN 53438 - 3 (F1)			



Medium	Polyester	
Media color	White	
WIDTH	NUMBER OF POCKETS	

WIDTH	HEIGHT	DEPTH	Number of pockets	Filter area	Recommended nominal air flow	Initial pressure drop
[mm]	[mm]	[mm]		[m²]	[m³/h]	[Pa]
<b>592</b>	<b>592</b>	360	6	2,6	3.400	60
490	592	360	5	2,1	2.700	60
287	592	360	3	1,3	1.700	60
592	287	360	6	1,2	1.600	60
592	490	360	6	2,1	2.700	60
287	287	360	3	0,6	800	60
592	892	360	6	3,9	5.100	60
490	892	360	5	3,2	4.200	60
287	892	360	3	1,9	2.500	60

## **Product benefits:**

- Progressively structured filter medium made of shatter-proof synthetic fibres
- Thermally welded, self-supporting continuous pockets with optimal distribution of incoming flow (pocket-fitting)
- Edge welding for higher density and pressure load
- Filter media tested according to OEKO-TEX® Standard 100 for harmful chemical content (17.0.25812)
- The optional BIOSTATIC version can be used when hygiene demands are high and in environments with increased air humidity
- Tested for paint compatibility by Fraunhofer IPA institute (doesn't apply to the biostatic version)
- For use in air-conditioning and ventilation systems of all kinds as well as in painting technology

# Initial pressure drop 592x592x360x6poc.

#### 90 Initial pressure drop [Pa] 60 30 2.100 2.600 3.100 3.600 4.100 1.600 Air flow [m³/h]

# **Versions:**

- Plastic frame: 25 mm
- Metal frame: 20 mm, 25 mm
- Special sizes on request
- Version with plastic frame fully incinerable
- Optional with foamed hygiene gasket
- Optional BIOSTATIC version: the ingredient located within the synthetic fibers "Silane Quaternary Ammonium Salt" (BIOCIDE) prevent odors and the formation of microorganisms on the filter which is harmful to the health





### Notice:

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifikations without notice.

www.volzfilters.com