

Pocket filter
V-Series PM10 55% V50
 592 x 592 x 600 8 poc.



Filter class acc. to ISO 16890	Particle efficiency	Energy consumption	Energy class
EN 779:2012			Threshold reference scale year 2019: (RS 4/C/001-2019)
ISO ePM10 55% M5	ePM ₁ 6 % ePM _{2,5} 20 % ePM ₁₀ 55 %	700 kWh/year	C




Similar to picture

Operating conditions:

Max. humidity resistance	100%
Max. temperature	70°C
Recommended final pressure drop	300 Pa
Potential nominal air flow (short term usage possible)	1,25 x nominal air flow
Fire behaviour	DIN 53438-3 (F1)

Medium High performance nonwoven fabric
 Media color Brown




Please note: in EUROVENT database, the depth of the model is extended by 25 mm

WIDTH	HEIGHT	DEPTH	Number of pockets	Filter area	Recommended nominal air flow	Initial pressure drop
[mm]	[mm]	[mm]		[m ²]	[m ³ /h]	[Pa]
592	592	600	8	5,7	3.400	65
490	592	600	6	4,3	2.600	65
287	592	600	4	2,8	1.700	65

Product benefits:

- Multi-layer structure of the filter media
- Shatter-proof synthetic fibres
- Welded continuous pockets
- Pockets hold their form
- High dust holding capacity and durability
- Very robust inherently rigid construction
- V-shaped pockets allow better air flow
- Effective use of the filter area
- Testing for paint compatibility by Fraunhofer IPA
- For use in air-conditioning and ventilation systems of all kinds as well as in painting technology

Initial pressure drop 592x592x600x8poc.



Versions:

- Plastic frame: 25mm
- Metal frame: 25mm
- With plastic cover sticks
- Version with plastic frame fully incinerable
- Optional with foamed hygiene gasket



Notice:

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.