

Technical data sheet

Filter material

MEDIsyntex 20



Similar to picture

PROPERTIES:		
Classification acc. to EN 14683:2019:		Type II
Bacterial Filtration Efficiency (BFE)	EN14683:2019	99,96%
Breathability (Differential Pressure):	EN14683:2019	< 40 Pa
Max. temperature:		70°C
Max. humidity resistance:		100%

COMPOSITION:	
Outer layer:	Polypropylene uncolored (Spunbonded 25g/m ²)
Middle layer:	Polypropylene blue (Meltblown 23g/m ²)
Inner layer:	Polypropylene uncolored (Spunbonded 15g/m ²)

AVAILABLE DIMENSIONS:	
Roll width:	200 mm ± 2 mm
Roll length:	500 m ± 0,5 m

Product Benefits:	
➤	<i>The medium is suitable for the production of medical face masks type II (EN14683: 2019), which are intended for use by medical professionals in medical facilities to protect the entire work environment</i>
➤	<i>The non-woven material consists of 3-layer connected fleeces</i>
➤	<i>Inner layer is very soft and skin-friendly</i>
➤	<i>Middle layer ensures good filtration</i>



Notice:

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.