

Compact filter PM10 65%



Filter class acc. to ISO 16890 EN 779:2012	Particle efficiency	Energy consumption	Energy class <small>Threshold reference scale year 2019: (RS 4/C/001-2019)</small>
ISO ePM10 65% M6	ePM ₁ 20 % ePM _{2,5} 35 % ePM ₁₀ 65 %	1.200 kWh/year	D



Similar to picture


Operating conditions:

Max. humidity resistance	100 %
Max. temperature	60 °C
Recommended final pressure drop	650 Pa
Max. airflow (Full size 592 x 592 x 292)	5.000 m ³ /h
Fire behaviour	DIN 53438 - 3 (F1)

Medium

High performance nonwoven fabric

Media color




WIDTH [mm]	HEIGHT [mm]	DEPTH [mm]	Number of V's	Filter area [m ²]	Recommended nominal air flow [m ³ /h]	Initial pressure drop [Pa]
592	592	292	4	19	3.400	90
490	592	292	4	15,0	2.700	90
287	592	292	4	9,5	1.700	90

Product benefits:

- Shatter proof synthetics fibres
- High dust holding capacity and service life
- The pleated filter packs are arranged in a V-shape
- Stable construction due the ultrasonic welded plastic housing
- Suitable for high air flows
- Filter media tested according to OEKO-TEX® Standard 100 for harmful chemical substances (17.0.25812)
- For use in air-conditioning and ventilation systems of all kinds as well as in painting technology

Initial pressure drop 592x592x292



Versions:

- All frame components are made from plastic
- Standard sizes with depth 292 mm
- Available option with abrasion-resistant hygiene-gasket
- Available option as **biostatic version**: the biostat agent "Silver-phosphate-Glass" (BIOCIDE) prevents odors and the formation of microorganisms on the filter which is harmful to the health



Notice:

All information and illustrations are sole property of Volz and are provided to the best of our company's knowledge. Yet our company does not take over any warranty for the completeness and/ or correctness and cannot be held liable for any damage occurring to the recipient through the use or through her or his trust in the completeness and/ or correctness of the information. The given data are mean values with tolerances due to normal production variations and do not release the recipient from own checks, investigations and test. Furthermore, all data serve as service description and shall not be interpreted as a warranty for composition or service life. Volz reserves the right to change specifications without notice.